



LayFlash

Fast setting patching compound

PRODUCT DESCRIPTION: LayFlash is a very fast setting mortar designed for emergency repair and installation jobs.

USES: Repair of roads, concrete floors, concrete tanks and the like. It is particularly useful where traffic must be kept flowing. LayFlash will accept vehicle traffic in 20 minutes. It can also be used for quick installations or anchoring of poles and equipment and for plugging water flow from leaking concrete water holding structures.

ADVANTAGES: LayFlash produces an easily troweled mortar that is fast setting, easy to use, non shrink, and needs only the addition of water. LayFlash is very effective in road repair whenever a minimum disruption to traffic is required.

LIMITATIONS: Follow up repair work with a more durable material such as epoxy is recommended.

COMPOSITIONS AND MATERIALS: Special formulation of Portland cement, graded silica, and other compatible modifiers.

PACKAGING: Packaged in 20 Kg. and 8 Kg. moisture resistant, multi-wall paper bags.

COLORS: White or gray.

TECHNICAL DATA:

Results

Initial Set 8 minutes

Final Set 12 minutes

INSTALLATION:

Surface Preparation: All surfaces must be clean and free of dust, grease, sealants and foreign matter.

Application: Mix with 3-4 liters of water and apply with conventional trowel. LayFlash may be used from 12mm to 50mm thick. If the depth of the hole is greater than 50mm add LayFlash in cycles of different layers. Allow each layer to set for a minimum of 1 hour before priming and placing the next layer.

Precautions: Portland cement is an irritant. Avoid contact with skin. In case of contact wash thoroughly with water. For eyes, get medical attention. Keep out of reach of children.

Cleaning: Wash with water.

Storage Life: One year if stored in cool, dry location. Do not expose to moisture. Close partially used bags tightly.

Email: laymaster@laymaster.net

*All material is Copyright Lay Master Inc. and may not be reproduced without written permission
Specifications subject to change without notice.*

Ver. 1/2004