



LayCure W

Concrete Curing Agent Wax based

PRODUCT DESCRIPTION: LayCure W is a wax based emulsion that is used as a curing compound for concrete surfaces. It acts as a sealant to encapsulate water into structure to allow complete hydration of cement. It forms a thin film over surfaces and dries up fast for immediate sealing

USES: Curing of concrete floors, columns, slabs, precast elements and other masonry structures.

ADVANTAGES: LayCure W forms an efficient moisture barrier for optimum curing of concrete, VOC compliant and is easy to remove after application.

LIMITATIONS: Must be removed before subsequent coating of concrete surface.

COMPOSITIONS AND MATERIALS: Wax based emulsion.

PACKAGING: Packaged in 30 Lit plastic Jerrycan.

APPLICABLE STANDARDS: LayCure W meets or exceeds ASTM 1315-00, ASTM C-309-98a Type 1 Class A, and ASTM C156 and ASTM C-1151

TECHNICAL DATA: LayCure W performs equally well on porous and non-porous surfaces. LayCure W is non-staining and water washable.

INSTALLATION:

Surface Preparation: All surfaces must be clean and free of dust, grease, sealants and foreign matter.

Application: Apply as soon as the concrete sets. Evenly apply fine spray held at approximately 50 cm from surface. Apply in a thin continuous film. Apply another coat if necessary. Do not apply in windy weather. LayCure W can be cleaned easily from surface by scrubbing or removal with a jet of hot water. Allow at least 7 days of curing. Removal of LayCure W is not necessary unless further coating is specified for the concrete surface.

Precautions: Avoid contact with skin. In case of contact wash thoroughly with water. For eyes, get medical attention. Keep out of reach of children.

Cleaning: Wash with water. After 7 days, it can be removed mechanically or with a hot jet of water or steam.

Storage Life: One year if stored in cool, dry location. Close partially used containers tightly.

Email: laymaster@laymaster.net

*All material is Copyright Lay Master Inc. and may not be reproduced without written permission
Specifications subject to change without notice.*

Ver. 1/2004