



LayStone Seal

Stone and Masonry Protection Compound

PRODUCT DESCRIPTION: LayStone Seal is an impregnating agent that is used for the protection of stone, bricks, concrete, natural stone and quarry tiles. It impregnates siliceous surfaces to provide a water-repellent surface that prevents aging and erosion caused by water and chemicals.

USES: Used on walls and floors to protect natural stone, concrete surfaces, pavers, bricks, etc.

ADVANTAGES: LayStone Seal is a solvent based liquid. It prevents chemicals from getting absorbed by the stone by stopping the water that can carry them into the stone. It penetrates several millimeters into the stone surface to provide extra protection without affecting the water permeability and breathability of the stone.

COMPOSITIONS AND MATERIALS: Special formulation of waxes.

PACKAGING: Packaged in 20 Kg drum

COLOR: Clear.

TECHNICAL DATA: LayStone Seal does not require the use of primer or surface conditioner; performs equally well on porous and non-porous surfaces, for use with most types of natural stone and concrete surfaces. LayStone Seal is non-staining.

INSTALLATION:

Surface Preparation: All surfaces must be dry, clean and free of dust, grease, sealants and foreign matter.

Application: The product is supplied as a ready to use solution that can be applied by flooding, spraying or pouring, but not with a brush. It can be diluted with water at 2:1 to 1:1 ratio, however, its effectiveness will be consequently reduced.

The freshly treated surface should be protected from rain for at least 8 hours.

Coverage

0.2 to 1.5 lit/m² depending on surface porosity.

Cleaning: Wash with water.

Storage Life: One year if stored in cool, dry location.

MAINTENANCE: LayStone Seal is maintenance-free. Its service life extends for more than 10 years.

Email: laymaster@laymaster.net

*All material is Copyright Lay Master Inc. and may not be reproduced without written permission
Specifications subject to change without notice.*

Ver. 1/2004